

OAK BISBEE

Oak Bisbee is a 3-strip floor with moderate color variations and a brown stain. May contain minor knots.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	133NABEK5MUW 0	Wood Species	White Oak	Moisture	EN13183	7%±2%
EAN Code	7393969034180	Design	3-strip	content		
Surface Treatment	Silk matte finish	Range	Kährs Avanti	Minimun Mean Density kg/m ³ >500 kg/m ³		
Dimensions	95 3/8 x 7 7/8 x 1/2"	Collection	Tres Collection	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	54 lbs	Resandable	2 times	Formaldehyde Emission	EN717-1	E1
Area per Package	36.6 sqft	Natural/Stained	Stained			
Area per pallet (m²)	0 sqft	Brinell Value	3,7	Content PCP	CEN/TR1482	3 ≤ 5 x 10-6n
Package info	Packages may contain start and stop boards.	Joint	Woodloc® 5G	Breaking EN Strength N/mm ²	EN1533	NPD
		Floor heating	Yes			
DETAIL DESCRIPTION			20 years	Thermal	EN12664	0,14 W/mK
Naturally occuring wood colour variations allowed, from light to dark brown. The product includes medium sound and black knots. Knots may vary in size and numbers.		Wear-layer material	Hardwood	Conductivity		
		Wear-layer thickness	7/64"	Thermal Resistance R-Value .09 (m2K/		.09 (m2K/W)
		Core material	Pine/Spruce lamella	Biological Durability	EN350-2	Class 1
		Thickness	1/2"	CARB2		Compliant
COLOR CHANGE		Installation method	Floating, Glue-Down			compliant

Stained product - noticable color change over time.





Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.