

SAFETY DATA SHEET

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

Product Identifier : **ARDEX SX™ Caulk**
Product ID No. : 1695297
Trade Name/Synonyms : ARDEX SX
Material Use : 100% Silicone Sealant for Tile and Stone Applications.
Uses Advised Against : Use only as recommended in the product's Technical Data Sheet.
Manufacturer's name and address: **Supplier's name and address:**



Refer to Manufacturer

ARDEX L.P.
400 Ardex Park Dr.
Aliquippa, PA 15001 USA

Information Telephone No. : (888) 512-7339 or (724) 203-5000
Website Address : <http://www.ardexamericas.com>
24 Hr Emergency Telephone # : CHEM-TEL: 1-800-255-3924 OR 1-813-248-0585 (call collect)

SECTION 2 – HAZARDS IDENTIFICATION

GHS Classification per 29 CFR 1910.1200 (OSHA HCS 2012) and HPR (WHMIS 2015)

Skin Sensitization, Category 1
Serious eye damage/eye irritation, Category 2B

GHS Pictograms



Signal Word

Warning.

Hazard Statements

May cause an allergic skin reaction.
Causes eye irritation.

Precautionary Statements

Avoid breathing dust/vapors. Wear protective gloves/eye protection. Wash hands and exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Dispose of contents / container in accordance with federal, state, and local laws. Do not allow product to enter drains.
During normal usage of the product as recommended, airborne dusts and mists will not be present. See Section 7 (Handling and Storage) for further details.

Hazards Not Otherwise Classified

None.

% with Unknown Acute Toxicity

25 % of this product consists of ingredients with unknown acute toxicity.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS #	% (by weight)
Limestone	1317-65-3	25-50

Polydimethyl siloxane	63148-62-9	12.7
Vinyl tris(methylethylketoxime) silane	2224-33-1	2-12
Fumed silica	68611-44-9	2-12
Titanium dioxide	13463-67-7	≤2.5
Aminoalkoxysilane*	1760-24-3	≤2.5
Crystalline silica, quartz	14808-60-7	≤2.5

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.

*Low levels of Methanol (CAS No. 67-56-1) are released from this product as it undergoes reaction with moisture in the air.

SECTION 4 – FIRST AID MEASURES

- General** : Call a Poison Center or doctor if you feel unwell.
- Inhalation** : Remove person to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.
- Skin contact** : Remove/Take off all contaminated clothing. Wash with plenty of soap and water. If irritations or symptoms develop, seek medical attention/advice.
- Eye contact** : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
- Ingestion** : Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.
- Notes for Physician** : Treat symptomatically.

Signs and symptoms of short-term (acute) exposure

- Inhalation* : Under normal conditions of use, not expected to cause respiratory symptoms.
- Skin* : Symptoms may include mild redness or itching.
- Eyes* : Symptoms may include redness, itching, or pain.
- Ingestion* : Symptoms such as gastric pain, nausea, vomiting, and diarrhea may occur.

Effects of long-term (chronic) exposure

- : Prolonged exposure to the skin may cause a sensitization reaction in some individuals, where subsequent exposures may result in an allergic skin reaction.

Indication of need for immediate medical attention or special treatment

- : Difficulty breathing persists after removing the person to fresh air.
Any exposure to the eye which causes irritation.
Persistent itching, rashes, or hives.

SECTION 5 – FIRE FIGHTING MEASURES

- Suitable extinguishing media** : Carbon dioxide, dry chemical powder, alcohol-resistant foam or water fog.
- Unsuitable extinguishing media** : Water jet may spread the burning material.
- Hazardous combustion products** : Carbon monoxide, carbon dioxide, as well as other toxic vapors and gases which are common to thermal degradation of organic compounds.
- Special fire-fighting procedures/equipment** : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. After fires have been extinguished, carefully clean all equipment and surfaces exposed to fumes.
- Environmental precautions** : Do not allow material to enter drains or contaminate ground water system.
- Fire hazards/conditions of flammability** : Not flammable under normal conditions of use. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.
- Flammability classification (OSHA 29 CFR 1910.1200, WHMIS 2015)** : Not flammable.
- NFPA Rating** : 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe

*Health: *2 Flammability 1 Instability 0 Special Hazards: None*

SECTION 6 – ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Restrict access to area until completion of clean-up. All persons dealing with clean-up should wear the appropriate chemically protective equipment.
- Protective equipment** : Refer to Section 8 for additional information on acceptable personal protective equipment.
- Emergency Procedures** : This product contains only traces of Methanol, a chemical requiring EPA notification for spills exceeding the Reportable Quantity for Methanol. In case of a chemical spill, call the emergency telephone number listed in Section 1.
US CERCLA Reportable quantity (RQ): Methanol, 5000 lbs.
- Methods and materials for containment and cleaning up** : Ventilate area of release. Stop spill or leak at source if safely possible. Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later disposal (see Section 13). Residual of product, while still wet, can be cleaned up with warm soapy water. Notify the appropriate authorities as required.
- Prohibited materials** : None known.
- Environmental precautions** : Do not allow product to enter drains or waterways. Do not allow material to contaminate ground water system.
- Reference to other sections** : See Section 13 for disposal information.

SECTION 7 – HANDLING AND STORAGE

- Safe handling procedures** : Wear suitable protective equipment during handling. (See Section 8.) Observe good hygiene standards. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Avoid contact with eyes, skin, or clothing. Avoid repeated or prolonged skin contact. Avoid breathing vapors or mists of this product. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used. Once a person is sensitized, no further exposure to the material that caused the sensitization should be permitted. Sanding and grinding dusts may be harmful if inhaled. When removing this product (e.g. during a renovation), wear safety goggles and respiratory protection from dust due to blasting, chipping, or mechanically pulverizing. Wear protective clothing to prevent skin contact. Promptly remove any clothing that becomes contaminated. Clean contaminated clothing before reuse. Keep container tightly closed.
- Storage requirements** : Store in a cool, dry, well-ventilated area. Store away from heat and open flame. Avoid storing in direct sunlight. Store in original container. Keep tightly closed when not in use. Do not reuse empty container without commercial cleaning or reconditioning.
- Incompatible materials** : See Section 10.
- Special packaging materials** : Always keep in containers made of the same materials as the supply container.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

- Permissible Exposure Limits** : No exposure limits have been established for the product itself. Below are exposure limits for the components in the product.

Ingredients	CAS #	ACGIH TLV		OSHA PEL	
		TWA	STEL	PEL	STEL
Limestone	1317-65-3	N/Av	N/Av	15 mg/m ³ (total dust); 5 mg/m ³ (respirable)	N/Av
Polydimethyl siloxane	63148-62-9	N/Av	N/Av	N/Av	N/Av
Vinyl tris(methylethylketoxime) silane	2224-33-1	N/Av	N/Av	N/Av	N/Av

Fumed silica	68611-44-9	N/Av	N/Av	N/Av	N/Av
Titanium dioxide	13463-67-7	10 mg/m ³	N/Av	15 mg/m ³	N/Av
Aminoalkoxysilane	1760-24-3	N/Av	N/Av	N/Av	N/Av
Crystalline silica, quartz	14808-60-7	0.025 mg/m ³ (respirable fraction)	N/Av	0.05 mg/m ³ (respirable) (final rule limit)	N/Av
Methanol (evolved slowly as product cures)	67-56-1	200 ppm	250 ppm	200 ppm	N/Av

Engineering Controls : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Ventilation should effectively remove and prevent buildup of any vapor generated from the handling of this product.

Personal Protection Equipment

Eye / face protection : Chemical goggles or safety glasses, as appropriate for the job.

Skin protection : Wear gloves which are impervious to the material. Materials such as nitrile rubber or Viton (fluorocarbon rubber) are recommended.

Body protection : Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact.

Respiratory protection : Under normal conditions of use with adequate ventilation, respiratory protection should not be necessary. If work process generates excessive quantities of vapor or dust, or exposures in excess of any PEL, wear an appropriate organic vapor respirator.

Site safety equipment : An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations : Avoid contact with eyes, skin and clothing. Avoid breathing vapors/dust. Do not eat, drink or smoke when using this product. Upon completion of work, wash hands and exposed skin thoroughly. Remove soiled clothing and wash it thoroughly before reuse. Clean all equipment and clothing at end of each work shift.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Paste	Appearance	: various colored paste
Odor	: Characteristic	Odor threshold	: N/Av
pH	: N/Av	Specific gravity	: 1.0 – 1.1
Boiling point	: > 284°F (140°C)	Coefficient of water/oil distribution	: N/Av
Melting/Freezing point	: N/Av	Solubility in water	: Not miscible
Vapor pressure (mm Hg @ 20°C / 68°F)	: N/Av	Evaporation rate (n-Butyl acetate = 1)	: N/Av
Vapor density (Air = 1)	: N/Av	Volatiles (% by weight)	: < 5 %
Volatile organic compounds (VOCs)	: 40 g/L SCAQMD 1168		
Particle size	: N/Av	Flammability classification	: Not flammable
Flash point	: > 200°F (93.3°C)	Lower flammable limit (% by vol)	: Not available
Flash point method	: N/Av	Upper flammable limit (% by vol)	: Not available
Auto-ignition temperature	: > 400°C	Decomposition temperature	: Not available
Viscosity	: N/Av	Oxidizing properties	: Not available

Explosion data: Sensitivity to mechanical impact / static discharge

: Not expected to be sensitive to mechanical impact or static discharge.

SECTION 10 – REACTIVITY AND STABILITY INFORMATION

Reactivity : Product cures by reacting slowly with moisture (humidity) in the air.

Stability : Stable under the recommended storage and handling conditions.

Hazardous reactions : Hazardous polymerization does not occur. Reacts with water. Reaction causes the formation of methanol.

Conditions to avoid : Extreme heat.

Materials to avoid and incompatibility : Strong oxidizing agents.

Hazardous decomposition products

: Methanol; also refer to combustion products in Section 5.

SECTION 11 – TOXICOLOGICAL INFORMATION

Routes of exposure : *Inhalation:* YES *Skin Absorption:* YES *Skin and Eyes:* Yes *Ingestion:* YES

Symptoms of exposure : See Section 4.

Calculated Acute Toxicity Estimates for the Product

Inhalation : N/A
Oral : > 5 000 mg/kg
Dermal : N/Av

Toxicological data : See below for individual ingredient acute toxicity data.

Ingredients	CAS No.	LC50 (4 hr), mg/L Inhalation, rat	LD50, mg/kg	
			Oral, rat	Dermal, rabbit
Limestone	1317-65-3	N/Av	6450	N/Av
Polydimethyl siloxane	63148-62-9	N/Av	N/Av	N/Av
Vinyl tris(methylethylketoxime) silane	2224-33-1	N/Av	N/Av	N/Av
Fumed silica	68611-44-9	N/Av	> 5 000	N/Av
Titanium dioxide	13463-67-7	> 6.82	> 24,000	> 10,000
Aminoalkoxysilane	1760-24-3	1.49 - 2.44 (1 hr)	2413	>2009 (rat)
Crystalline silica, quartz	14808-60-7	N/Av	> 22 500	N/Av
Methanol	67-56-1	131.25	143	17100

Skin corrosion or irritation : May cause slight irritation to skin.

Serious eye damage / eye irritation : Causes irritation to eyes.

Respiratory or skin sensitization : Contains Vinyl tris(methylethylketoxime)silane, which is known to cause skin sensitization reactions. See precautions recommended for persons with a history of skin sensitization or asthma in Section 7.

Germ cell mutagenicity : None known.

Carcinogenic status : This product contains Crystalline silica (quartz), which is listed as a known human carcinogen (via inhalation) by IARC (Group 1) and NTP. Some colors contain Titanium dioxide and/or Carbon black. Titanium dioxide is suspected to be carcinogenic by inhalation (IARC 2B). Carbon black is suspected to be carcinogenic by inhalation (IARC 2B) and classified as a carcinogen by NTP. Under normal conditions of use, this product will not produce airborne dust. Avoid operations such as grinding, sanding or sawing without proper dust abatement equipment. See Section 7 for more information.

Reproductive toxicity : None known.

Specific Target Organ Toxicity, Single Exposure : None known.

Specific Target Organ Toxicity, Repeated Exposure : None known.

Aspiration hazard : None known.

Additional information : N/Av

SECTION 12 – ECOLOGICAL INFORMATION

Environmental effects : The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

Ecotoxicity : No data available.
Biodegradability : No data available.
Bioaccumulative potential : No data available.
Mobility in soil : No data available.
PBT and vPvB assessment : No data available.
Other adverse effects : No data available.

SECTION 13 – DISPOSAL CONSIDERATION

- Handling for disposal** : Handle waste according to recommendations in Section 7.
- Methods of disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.
- Packaging** : Handle contaminated packaging in the same manner as the product.
- RCRA** : For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14 – TRANSPORTATION INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	None	This product is not regulated according to Canadian TDG regulations.	None	None	None
TDG Additional Information	None				
49 CFR/DOT	None	This product is not regulated according to US DOT regulations.	None	None	None
49 CFR/DOT Additional Information	None				

IATA : Not regulated for Air Transport
IMDG : Not regulated for Ocean Transport

SECTION 15 – REGULATORY INFORMATION

Canadian Information:

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR). This SDS contains all of the information required by the HPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on either the Domestic Substances List (DSL) or the Non- Domestic Substances List (NDSL).

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): Methanol, 5000 lbs.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:

Immediate (Acute) Health Hazard

Chronic Health Hazard

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: Methanol.

U.S. State Right to Know Laws

California Proposition 65:

- ⚠ **WARNING:** This product can expose you to chemicals including Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Other State Right to Know Laws:

Ingredient on State RTK Law?	CAS #	CA	MA	MN	NJ	NY	PA	RI
Limestone	1317-65-3	No	Yes	No	Yes	No	Yes	Yes
Titanium dioxide	13463-67-7	No	Yes	Yes	Yes	No	Yes	Yes
Crystalline silica, quartz	14808-60-7	No	Yes	Yes	Yes	No	Yes	Yes
Methanol	67-56-1	Yes	Yes	No	Yes	Yes	Yes	Yes

SECTION 16 – OTHER INFORMATION

HMIS Rating : * - Chronic Hazard 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe
Health: 2 Flammability 1 Physical Hazard 0 PPE: Gloves, safety glasses

Legend :

- ACGIH: American Conference of Governmental Industrial Hygienists
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- DOT: Department of Transportation
- DSL: Domestic Substances List
- EPA: Environmental Protection Agency
- GHS: Globally Harmonized System
- HPR: Hazardous Products Regulations
- IARC: International Agency for Research on Cancer
- Inh: Inhalation
- N/Av: Not Available
- N/Ap: Not Applicable
- NIOSH: National Institute of Occupational Safety and Health
- NTP: National Toxicology Program
- OSHA: Occupational Safety and Health Administration
- PEL: Permissible exposure limit
- RCRA: Resource Conservation and Recovery Act
- SARA: Superfund Amendments and Reauthorization Act
- STEL: Short Term Exposure Limit
- TDG: Canadian Transportation of Dangerous Goods Act & Regulations
- TLV: Threshold Limit Values
- TSCA: Toxic Substance Control Act
- TWA: Time Weighted Average
- WHMIS: Workplace Hazardous Materials Identification System

Disclaimer of Liability

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

No warranty of any kind is given or implied. ARDEX L.P. will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein.

Prepared By:
ARDEX L.P.
 400 Ardex Park Drive
 Aliquippa, PA, U.S.A.
 15001

(724) 203-5000
 Visit our Website: <http://www.ardexamericas.com>

Revision date: : 26-Oct-2020

End of Document